



Power Supply	5V Vbus (PC) mini USB A to B type or AC/DC Adapter 5V/1A
Unit	1 Unit for LINEA-PRO & iPod touch®
LEDs	1 Double LEDs (Green & Red) for status of charging LINEA-PRO & iPod touch Red LED - Charging; Green LED - Ready / Without Devices
Operating Environment	Temperature: 0 - 40° C Humidity: 35 - 85% RH
Storage Environment	Temperature: -5° C - 40° C Humidity: 10 - 90% RH
Dimensions	90mm (L) x 38mm (H) x 62mm (W)
Weight	50 grams without devices

Power Supply	AC/DC Adapter 24V/2A
Unit	5 Units for LINEA-PRO & iPod touch®
LEDs	5 Double LEDs (Green & Red) for status of charging LINEA-PRO & iPod touch Red LED - Charging; Green LED - Charging Ready / Without Devices
Operating Environment	Temperature: 0 - 40° C Humidity: 35 - 85% RH
Storage Environment	Temperature: -5° C - 40° C Humidity: 10 - 90% RH
Dimensions	260 mm (L) x 33mm (H) x 89mm (W)
Weight	450 grams without devices

Power Supply	AC/DC Adapter 24V/2A
Unit	10 Units for LINEA-PRO & iPod touch®
LEDs	10 Double LEDs (Green & Red) for status of charging LINEA-PRO & iPod touch Red LED - Charging; Green LED - Charging Ready / Without Devices
Operating Environment	Temperature: 0 - 40° C Humidity: 35 - 85% RH
Storage Environment	Temperature: -5° C - 40° C Humidity: 10 - 90% RH
Dimensions	260mm (L) x 33mm (H) x 168mm (W)
Weight	1300 grams without devices

Cidroid
Division of Nexus s.r.l.
Via Palmanova 24
20132 Milano
Italy
+39 (0)2 2666490

info@cidroid.com
www.cidroid.com

Preferred partner for Italy, Spain & Portugal

